



SPECIFICATIONS
 Current Rating: 1.0 Amps
 Insulator Resistance: 1000 Megohms Min.
 Withstanding Voltage: 300V AC/minute
 Temperature Range: -40~+105°
 Contact material: Brass
 Finish: Gold or Tin plated
 Insulator Material: PBT
 Soldering Temperature: +220°C, 10S max

OPERATION		~ 10	±0.15	DRAW		ROSE.W	2001.03.06	SCALE		
DESIGN		20 ~ 30	±0.30	CHECK		MICKY	2001.03.06	UNIT		mm
ANGLE		30 ~	±0.50	APPROVE		HELLEN	2001.03.06	SIZE		A4
DIM		± 2'		PROU.				SHEET		1/1
TOL				TITLE:		1.27mm Female Header Double Row Straight Dip Type		PART NO.		FH127H200-ST-2XXXP
CHANGE				P.C.B LAYOUT		SCONDAR ELECTRONIC LIMITED		森康达电子有限公司		
APPROVE				SCONDAR		SCONDAR ELECTRONIC LIMITED		SCONDAR ELECTRONIC LIMITED		
DATE		NEW		SCONDAR		SCONDAR ELECTRONIC LIMITED		SCONDAR ELECTRONIC LIMITED		
MODIFICATION DESCRIPTION				SCONDAR		SCONDAR ELECTRONIC LIMITED		SCONDAR ELECTRONIC LIMITED		
DATE		NEW		SCONDAR		SCONDAR ELECTRONIC LIMITED		SCONDAR ELECTRONIC LIMITED		
DATE		NEW		SCONDAR		SCONDAR ELECTRONIC LIMITED		SCONDAR ELECTRONIC LIMITED		
DATE		NEW		SCONDAR		SCONDAR ELECTRONIC LIMITED		SCONDAR ELECTRONIC LIMITED		